

SHACKLE SAFETY PIN BOW GRADE S

Capacities: 2 tonnes to 55 tonnes

- The most common shackles used in lifting applications
- High strength to size ratio
- Standard Grade S Yellow Pin
- Safety pin shackles are used for long-term or permanent applications or where the load may slide on the pin, causing rotation of the pin.

COMPLIES WITH AS2741



Size (mm)	WLL (t)	Type	Shape	Closing Method	DIA d (mm)	DIA PIN D (mm)	Inside Width W (mm)	Inside Length L (mm)	Width of Bow B (mm)	DIA Boss F (mm)	Approx Weight (kg)
13 x 16	2.00	Grade S	Bow	Safety Pin	13	16	21	48	33	33	0.44
16 x 19	3.20	Grade S	Bow	Safety Pin	16	19	27	61	43	40	0.79
19 x 22	4.70	Grade S	Bow	Safety Pin	19	19	32	72	51	48	1.26
22 x 25	6.50	Grade S	Bow	Safety Pin	22	25	37	84	58	54	1.88
25 x 29	8.50	Grade S	Bow	Safety Pin	25	29	43	95	68	60	2.78
29 x 32	9.50	Grade S	Bow	Safety Pin	29	32	46	108	74	67	3.87
32 x 35	12.00	Grade S	Bow	Safety Pin	32	35	52	119	83	76	5.26
35 x 38	13.50	Grade S	Bow	Safety Pin	35	38	57	133	92	84	6.94
38 x 41	17.00	Grade S	Bow	Safety Pin	38	41	60	146	98	92	8.79
45 x 51	25.00	Grade S	Bow	Safety Pin	44	51	73	178	127	110	14.99
51 x 57	35.00	Grade S	Bow	Safety Pin	51	57	83	197	146	127	20.65
63 x 70	55.00	Grade S	Bow	Safety Pin	63	70	105	267	184	152	41.05

